

**TOOLS**

December 2009

# HULTAFORS TOOLS INTRODUCES THREE NEW LASERS

## WITH SIMPLICITY AS THE COMMON THING.

**LINE LASER XL 2**

Small and flexible cross-line laser. Laser is auto-levelling with 2 diodes for vertical and horizontal lines. The lines can be switched separately or together to form a cross. There is an option to mechanically lock the pendulum to tilt the laser.

The laser is equipped with a transportation lock that locks the pendulum when the laser is not in use.

Makes jobs such as, measuring out walls, kitchens or when painting with two different colours, simpler.

- Auto-levelling  $\pm 5^\circ$ .
- Tolerance:  $\pm 1.0$  mm / m.
- Laser class: 2M/EN 60825-1.
- Wavelength: 2 x 635 nm.
- Operating range: r = 15m.
- Tripod thread: 5 / 8.

**FLOOR LASER FXL**

Floor laser has 4 laser lines at  $90^\circ$  to each other forming a cross in front of the unit. This allows you to add tiles in four directions. The lines will also continue behind the laser, which means that you can put tiles in the entire space with a single measurement.

The laser has adjustable feet for work on uneven surfaces, plus a 5mm spacer foot, which makes it possible to lay tiles underneath the unit. Makes it easier to lay tiles.

- Tolerance:  $\pm 0.3$  mm / m.
- Laser class: 2/EN 60825-1.
- Wavelength: 4 x 635 nm.
- Operating range: r = 10m per line.

**ROTATION LASER RL**

Horizontal auto-levelling rotation laser. The laser is equipped with a transportation lock that locks the pendulum when the laser is not in use.

Easy to operate - the laser is operated with two buttons at the top of the device. The advantage of this is that the laser will not move out of position when you press keys during operation.

The laser includes both a receiver and remote control which facilitates the use when the laser is used for longer distances and when you are working by yourself.

- Auto-levelling  $\pm 5^\circ$ .
- Tolerance:  $\pm 0.2$  mm / m.
- Laser class: 2/EN 60825-1.
- Wavelength: 1 x 635 nm
- Operating range: r = 30m respectively. 150m with the receiver.
- 2 speeds, 300, 600 rpm.
- Tripod thread 5 / 8.

## PRODUCT INFORMATION

Art. no.	Name	Model	Length	Width	Height	Qty/Pack	Weight	EAN code
409040	Line laser	XL-2	120 mm	65 mm	105 mm	1 pcs	400 g	7317844090405
409030	Floor laser	FXL	55 mm	235 mm	151 mm	1 pcs	650 g	7317844090306
409010	Rotation laser	RL	175 mm	130 mm	130 mm	1 pcs	1200 g	7317844090108

## ACCESSORIES - STAND

Strong tripod stand in anodized aluminium. Two of the stands are equipped with crank for height adjustment (408321, 408331).

Suitable for device with 5/8 thread. Individual adjustable legs.



## PRODUCT INFORMATION

Art. no.	Name	Model	Transport distance	Use height	Qty/Pack	Weight	EAN code
408321	Stand	S 130*	80 cm	75 – 130 cm	1 pcs	5,1 kg	7317844083216
408331	Stand	S 300*	120 cm	113 – 180 cm	1 pcs	6,5 kg	7317844083315
408341	Stand	B 140*	100 cm	90 – 140 cm	1 pcs	2,5 kg	7317844083414

\* Hand crank for height adjustment.

Dispatch from our warehouse: Immediately.